

RCC-M 2007 §B3500

Paramètre	Design 1	Design 2	Design 1	Design 2	Design 1	Design 2
	NIV0	NIV0	NIVC	NIVC	NIVD	NIVD
Af	19931.0	27560.0	19931.0	27560.0	19931.0	27560.0
Am	6896.0	8000.0	6896.0	8000.0	6896.0	8000.0
Cp	34.0	34.0	34.0	34.0	34.0	34.0
Dt	168.3	168.3	168.3	168.3	168.3	168.3
E	200000.0	220000.0	200000.0	220000.0	200000.0	220000.0
K	24.0	24.0	24.0	24.0	24.0	24.0
Ps	19.1	19.1	/	/	/	/
Ps	/	/	21.01	21.01	/	/
Ps	/	/	/	/	24.83E+00	24.83E+00
S	112.0	112.0	112.0	112.0	112.0	112.0
T_d	110.0	110.0	110.0	110.0	110.0	110.0
T_r	35.43	35.43	35.43	35.43	35.43	35.43
Tb	40.65	40.65	40.65	40.65	40.65	40.65
Te1	77.71	77.71	77.71	77.71	77.71	77.71
alpha	90.0	90.0	90.0	90.0	90.0	90.0
d	135.4	135.4	135.4	135.4	135.4	135.4
d'm	280.3	290.0	280.3	290.0	280.3	290.0
de	120.0	120.0	120.0	120.0	120.0	120.0
dm	135.4	135.4	135.4	135.4	135.4	135.4
dt	139.76	139.76	139.76	139.76	139.76	139.76
h	50.0	50.0	50.0	50.0	50.0	50.0
r	85.51	85.51	85.51	85.51	85.51	85.51
r_2	15.0	15.0	15.0	15.0	15.0	15.0
ri	67.8	67.8	67.8	67.8	67.8	67.8
tm	60.0	60.0	60.0	60.0	60.0	60.0
α	8.1e-4	8.1e-4	8.1e-4	8.1e-4	8.1e-4	8.1e-4
Ca	1.0	1.0	1.0	1.0	1.0	1.0
Cb	1.0	1.0	1.0	1.0	1.0	1.0
Fb	245.45E+03	245.45E+03	245.45E+03	245.45E+03	245.45E+03	245.45E+03
I	72.59E+06	72.59E+06	72.59E+06	72.59E+06	72.59E+06	72.59E+06
L_A	35.43	35.43	35.43	35.43	35.43	35.43
L_N	37.45E+00	37.45E+00	37.45E+00	37.45E+00	37.45E+00	37.45E+00
Pm	64.75E+00	75.3495	/	/	/	/
Qp	1.57E+03	1.57E+03	1.72E+03	1.72E+03	2.04E+03	2.04E+03
crit1	Verifie	Verifie	Verifie	Verifie	Verifie	Verifie
r_3	5.0	5.0	5.0	5.0	5.0	5.0